

Technical Data Sheet



PREMIUM WASH

Premium Wash has been formulated as an all round blanket and roller wash for 26" - 50" sheetfed presses. Premium Wash offers medium evaporation rate and excellent deep cleaning. Premium Wash is water miscible to aid in removing paper and coating pile from blankets.

For heavily linting stocks water can be added to Premium Wash to help flush out the paper fibres from the roller train. Premium Wash contains corrosion inhibitors and rubber rejuvenators to keep metal machine parts and rubber surfaces in prime condition.

For automatic blanket washing systems refer to Premium FD Wash (for automatic roller washers refer to Auto Wash). Premium Wash will not remove the image from unbaked positive plates even if left in contact with the plates overnight.

DIRECTIONS:

Blankets - Use a damp cloth to apply Premium Wash to the blankets or apply a wet sponge first over the blankets if there is a heavy layer of pile.

Rollers - Idle the press at washup speed. Apply a few squirts of Premium Wash to the rollers. Allow this to run in then engage the washup blade. Apply an even film of Premium Wash to the rollers until the washup blade runs clean. For paper fibres in the roller train try alternating water and Premium Wash or mix Premium Wash with 25% - 50% water.

Cloth Dampers - Apply Premium Wash with a squirt bottle and scrub the dampers with a brush to remove stubborn ink deposits. Rinse thoroughly with hot water until the water runs clean then scrape off the excess water.

For roller washing machines dilute 1 part Premium Wash with 4 parts water in a 5L container. Shake vigorously and use this mix on the spinning dampers until clean. Rinse with clean water.

HEALTH & SAFETY:

Premium Wash has no known long-term health affects (based on this products components) when used with reasonable care and with accepted practices of industrial hygiene. Premium Wash is flammable. Avoid breathing the vapours. Avoid skin contact as this product can dry out the skin.

PACKAGING:

20 Litre, 200 Litre metal drums

GSB Chemical Co. Pty. Ltd
ACN 004 355113
4 – 5 Beatrice Avenue
West Heidelberg Vic. 3081

Telephone: +61 03 9457 1125
Facsimile: +61 03 9459 7978
Internet: www.gsbchem.com.au
e-mail: info@gsbchem.com.au